




## Direct solenoid and solenoid pilot operated valves

Function	Port size	Flow (Max)	Individual Mounting	Series
<b>3/2 NO-NC</b>	<b>1/4" – 3/8"</b>	<b>2.0 Cv</b>	<b>Inline</b>	<b>53</b>

### OPERATIONAL BENEFITS

1. The 4-way pilot develops maximum shifting force both ways
2. Memory spring available
3. Balanced spool, immune to variations of pressure, also provides high flow
4. Short stroke with high flow
5. Bonded spool with minimum friction, shifting in a glass-like finished bore
6. Pilot with balanced poppet, high flow, short and consistent response times.
7. Wiping effect eliminates sticking
8. Long service life



### HOW TO ORDER

Port size	Pilot air	NC Valve	NO Valve
<b>1/4" NPTF</b>	Internal	53A-1AA- <b>XX-XXXX-XXX</b>	53A-2AA- <b>XX-XXXX-XXX</b>
<b>3/8" NPTF</b>		53A-1AB- <b>XX-XXXX-XXX</b>	53A-2AB- <b>XX-XXXX-XXX</b>
<b>1/4" NPTF</b>	External from 10 end	53A-1BA- <b>XX-XXXX-XXX</b>	53A-2BA- <b>XX-XXXX-XXX</b>
	from 12 end	53A-1CA- <b>XX-XXXX-XXX</b>	53A-2CA- <b>XX-XXXX-XXX</b>
<b>3/8" NPTF</b>	External from 10 end	53A-1BB- <b>XX-XXXX-XXX</b>	53A-2BB- <b>XX-XXXX-XXX</b>
	from 12 end	53A-1CB- <b>XX-XXXX-XXX</b>	53A-2CB- <b>XX-XXXX-XXX</b>

### SOLENOID OPERATOR

DM – D **XX X** – **X XX**

XX	Voltage	X	Wire length	X	Manual Operator	XX	Electrical connection
JA	110/50, 120/60	A	18"	1	Non locking	BA	Flying leads
JB	220/50, 240/60	B	24"	2	Locking	KA	Mini square connector
JC	24/60	J <sup>†</sup>	6"			KD	Mini square connector with light
FB	24VDC (1,8W)					JB	Rectangular connector
DA	24VDC (5,4W)					JD	Rectangular connector with light
DF	24VDC (12,7W)						

<sup>†</sup> For use with "J" and "K" type connectors

GM – G **XX X** – **X XX**

XX	Voltage	X	Wire length	X	Manual Operator	XX	Electrical connection
DC	24VDC (1,8W)	A	18"	1	Non locking	BA	Flying leads
DD	24VDC (2,5W)	B	24"	2	Locking	BT	Flying leads with light
DF	24VDC (4,0W)	C	36"			KA	Solenoid plug-in wire assembly
						KT	Solenoid plug-in wire assembly with light
						GA	MAC JAC solenoid plug-in wire assembly

### OPTIONS

53A-**X** A **A-XX-XXXX-XXX**

- For valve less base
- For memory spring

- Replace by **0**
- Replace by **5** (Normally closed)
- Replace by **6** (Normally open)



## Direct solenoid and solenoid pilot operated valves

### TECHNICAL DATA

<b>Fluid:</b>	Compressed air, vacuum, inert gases
<b>Pressure range:</b>	Internal pilot: 20 to 120 PSI (Memory spring option: 35-120 PSI) External pilot: Vacuum to 120 PSI
<b>Lubrication:</b>	Not required, if used select a medium aniline point lubricant (between 180F and 210F)
<b>Filtration:</b>	40μ
<b>Temperature range:</b>	0°F to 120°F (-18°C to +50°C)
<b>Orifice:</b>	8,5 mm
<b>Flow:</b>	1/4": Cv 1.7 – 3/8": Cv 2.0
<b>Coil:</b>	Epoxy encapsulated - Class A wires – 100% ED (specify mod. 0449)
<b>Voltage range:</b>	-15% to +10% of nominal voltage
<b>Protection:</b>	IP54 (GM pilot) – IP64 (DM pilot)
<b>Power:</b>	1,0 to 5,4W (Higher wattages available)

Options: BSPP threads

### DIMENSIONS

Shown with 3/8" and KA connector

